

ES - The ultimate color remover for efficient results

This product information is only intended as a guide to the handling of the product. Therefore, the ES METHOD cannot provide any guarantee for the achieved results. The user of the product shall perform tests and be responsible for the outcome.

ES, the advanced paint remover

Specially designed to dissolve epoxy paints and multiple layers of different paint types in a smooth and efficient manner. With its outstanding ability to dissolve organic materials, ES has impressed in all tests. Additionally, it is easily biodegradable, making it easy to handle, especially for removing epoxy paints from aluminum surfaces.

ES is the perfect two-step solution for vertical surfaces such as wooden facades and stripping multiple layers of paint from metal roofs. Its extended "open time" allows you to work calmly and at your own pace as it dries slowly. With its viscous consistency, it is ideal for situations where you need a product that stays on the surface and provides maximum effectiveness. This fantastic product solves a range of paint types, including alkyds, acrylics, epoxies, phenolic resins, polyvinyl acetate, styrene, urethane, amines, and cellulose lacquers. With ES, you have a solution for all your paint removal problems.

Here's how to use ES

Simply apply it externally in two steps, without working it in. Use a brush, roller, or high-pressure sprayer. The stripping time varies depending on the thickness of the paint, usually taking between 30 minutes and 24 hours. Then, simply use a natural sponge. Alternatively, scrape off the paint with a suitable tool or gently rinse the surface with a high-pressure jet of hot water (90°C) at a pressure of 150-300 bar. Please note that high-pressure water on wood may take weeks to dry. Be careful with plastic components and rubber gaskets, as they may get damaged.

Free shipping for online orders

Fast deliveries
Secure online shopping
We also accept Swish payment
Scan the QR code
Visit our online store
[Click here.](#)

Specifications

Article number: : 7636-001, 005, 025
Brand: ES METHOD
Size: 1l, 5l, 25l
Application tools: Brush, spray, putty knife
Delivery time (number of working days): 1-4



Recommended packaging materials

EPDM or natural rubber, if the temperature allows. Consumption ranges from 0.2 liters per square meter depending on the need. Do not dilute.

ES should be stored frost-free in its original packaging to maintain its quality. It has a shelf life of approximately 24 months in unopened packaging, providing you with long-lasting use. For your safety, we recommend using protective gloves, clothing, and safety goggles when handling the product.

Technical data

ES is a viscous liquid packaged in plastic drums of 5 or 25 liters. Its density is 0.99 kg per liter, and it has a slight solvent odor. The product contains n-butylpyrrolidone, which gives it its impressive capabilities.

Transport

During transportation, you can be assured. ES is not classified as hazardous goods, which means you don't need to worry about any special requirements or restrictions when moving the product.

ES METODEN



"CAPSULE IN; LIFT UP; WASTE DISPOSAL; REMOVE ALL MOURNING REMAINS; PAINT DIRECTLY ON A CLEAN AND DRY SURFACE."

+7 °C - + 35°C

ES METODEN complies with the CLP Regulation, (EC) 1272/2008 guidelines. [Read more.](#)

Warning

Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation

